

Excavator hook welded VABH-W 1,5t

Artikel-Nr: 7991208




Used as a lifting point for spreader bars, wire rope slings, round slings, lifting means: oval suspension ring.

- Can be combined with most commercial lifting means without additional connecting element.
- Patented markings for easy determination for withdraw of service.
- Robust, forged safety latch.
- Phosphated surface.
- Weld-on point can be used as excavator hook.
- Simple and fast welding installation.
- Material of weld-on-block 1.6541 (23MnNiCrMo52) Weld: Kehlnaht 4 (please observe user instruction).
- Area of application in ring plane: 150°, Area of application at lateral load: +45°, -45°
- corresponds with the test criteria: "GS-HM-36"

Welding should only be carried out by qualified persons according to ISO 9606-1. Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

Excavator hook welded VABH-W 1,5t

Artikel-Nr: 7991208



weight	0.85 kg	1.87 lbs
Nominal WLL	1500 kg	3300 lbs
T	26 mm	1"
A	7,5 mm	11/32"
B	76 mm	3"
C	115 mm	4-1/2"
D	111 mm	4-13/32"
E	70 mm	2-3/4"
F	21 mm	13/16"
I	38 mm	1-1/2"