

PowerPoint PP-B-1,5t-M16

Artikel-Nr: 7989523




- **Double ball bearing** is the optimal solution for turning and flipping operations under full load (not suitable for permanent turning under load).
- **Lifting points pivots 360°.**
- **Large distance between bolt-on surface and load to avoid damage.**
- **Rotatable at nominal WLL, 90° to the bolt-on direction** Lowest kinking possibility due to cardan joint.
- **Suspension ring with enlarged pivoting area.**
- Clear marking of the minimum WLL for all loading directions.
- Marking with requested torque moment and nominal WLL with a safety factor of 4:1 (MRL 2006/42/EG) and 5:1 (ASME B 30.26).
- Tested and certified by DGUV, Testing specifications: GS-HM-36:2023-06, Certificate-No.: HM 240065
- Significant product characteristics of the PP-S, PP-B and PP-VIP are subject to property right claims. ● Quick and easy installation with just one bolt connection.
- Hand tightening with appropriate wrench is sufficient for a singular lift.
- Please observe torque instructions when lifting point is permanently installed resp. at constant swivelling operations and tilting/ turning actions.

Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

PowerPoint PP-B-1,5t-M16

Artikel-Nr: 7989523



weight	0.50 kg	1.10 lbs
Nominal WLL	1500 kg	3300 lbs
T	115 mm	4-1/2"
A	11 mm	7/16"
B	65 mm	2-9/16"
C	35 mm	1-3/8"
D	46 mm	1-13/16"
E	41 mm	1-5/8"
F	24 mm	15/16"
G	49 mm	1-15/16"
M	M16 mm	M16
N	15 mm	19/32"