

PSA-INOX-STAR-Eyebolt M16 with L=120 mm

Artikel-Nr:




- **Lifting points pivots 360°**
- **Fall arrest protection.** Statement for number of persons which can be secured.
- **Non removable special bolt**(this reduces the risk of improper standard bolts).
- Available as: – Standard Metric Thread (DIN EN 13) – Coarse Pitch Thread UNC (ANSI B1.1)
- According to EG Directive 89/686/EWG. Exceeds the requirements of DIN EN 795. Marking corresponds to DIN EN 365.
- Tested and certified by faculty PSA of DGUV.
- DGUV approval for attachment to steel and with blind rivet nuts.
- **Pentagonal shape for a clear determination to common lifting points (i.e. eye bolts).** Body and bolt made out of Duplex Steel 1.4462 (high resistancy in sea water and in environment with a high concentration of chlorine ions. Component is allowed to be used in outdoor applications.
- Quick and easy installation with just one bolt connection.
- Hand tightening with appropriate wrench is sufficient for a singular lift.

Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

PSA-INOX-STAR-Eyebolt M16 with L=120 mm

Artikel-Nr: 7912515



weight	0.53 kg	1.17 lbs
T	50 mm	1-31/32"
B	15 mm	19/32"
C	14 mm	9/16"
D	35 mm	1-3/8"
E	44 mm	1-3/4"
G	45 mm	1-25/32"
I	22 mm	7/8"
K	65 mm	2-9/16"
L	120 mm	4-3/4"
M	M16 mm	M16
N	10 mm	3/8"