



PRODUCT TECHNICAL AND COMMERCIAL DATA SHEET

Description

PULMIC INDUSTRIAL 15

Ref. 18421

Electric sprayer for the application of disinfectant, bactericidal, virucidal products and ozone treatments.

New 25V MAX 2.5Ah batteries for extended autonomy.

Tariff heading: 84244100

EAN: 8435128268322



8435128268322

Product photo

INDUSTRIAL 15

15 L

4.0 gal

7 BAR

100 psi



ELECTRIC

TECHNOLOGY

Li-ion



DRAIN CAP & FILTER



REMOVABLE BATTERY




PADDED STRAPS



QUICK CONNECT



INDUSTRIAL






**Product specifications**

Tank	Color	White
	Material	Polypropylene
	Filling opening diameter	130 mm
	Capacity	15 L
	Straps	Adjustable straps, 4 cm wide and 120 cm long, with padded shoulder pads
	Carrying handle	Sí
Pump	Compression and pumping system	Electric, using a diaphragm pump / brushed DC motor
	Flow rate	See table according to nozzles (p. 3)
	Pressure	See table according to nozzles (p. 3)
Control unit	Electronic regulation of the pump voltage, providing 3 different pressure levels and optimizing battery autonomy. 3S system	
Diaphragm	Made of Santoprene	
Hose	Material	PVC with polyester mesh reinforcement
	Length	120 cm
Handle	Material	Latón, con filtro.
	Size	15 x 4 cm
Battery	25V MAX 2,5Ah	LiCoO ₂
	Triple charger (european)	Input 100-250V AC 50/60 Hz Output 25,2V DC 1,4 ^a
	Temperature range	-20 °C ~ 60 °C
	Weight	0.37 kg
	Autonomy	Ver tabla según boquilla (Pág. 3)
Lance	Material	Stainless steel
	Length	42,5 cm
Nozzles	Adjustable industrial nozzle	
	Red industrial nozzle 0°	
	Green industrial nozzle 25°	
	White industrial nozzle 40°	
Attached documentation	Instruction manual	



Nozzles

Boquilla Nozzle Buse Bico Ugello Dysza Сопло فوهة		Velocidad Speed Vitesse Velocidade Velocità Prędkość Скорость سرعة	Presión Pressure Pression Pressão Pressione Ciśnienie Давление ضغط		Ángulo Angle Angle Ângulo Angolo Kąt Угол زاوية	Caudal Flow Débit Fluxo Flusso Przepływ Поток تدفق		Capacidad/batería Capacity/battery Capacité/batterie Capacidade/bateria Capacità/batteria pojemność/baterię Емкость/аккумулятор السعة / البطارية		Autonomía total Total autonomy Autonomie totale Autonomia total Autonomia totale Całkowita autonomia Полная автономия الحكم الذاتي الكامل
			bar Бар	psi Пси		L/min л/мин	gpm гал/мин	L л	gal гал	min. Мин.
		1	2.5	36	25°	1.8	0.47	342	90.3	190
		2	4.5	65	25°	2.2	0.58	275	72.7	125
		3	5.5	79	25°	2.4	0.63	264	69.7	110
		1	3	43	0°	1.8	0.47	315	83.2	175
		2	5	72	0°	2.1	0.55	262	69.2	125
		3	6	87	0°	2.2	0.58	220	58.1	100
		1	1.5	21	max. 70°	2	0.52	440	116.3	220
		2	3	43	max. 70°	2.4	0.63	348	91.9	145
		3	3.5	50	max. 70°	2.8	0.73	322	85.1	115
		1	2.8	38	40°	1.9	0.50	332	87.72	175
		2	4.4	64	40°	2.3	0.61	334	88.23	145
		3	5.8	84	40°	2.5	0.66	325	85.86	130

Las pruebas se realizan alternando 2 min en marcha y 1 min parado.

Tests are carried out alternating 2 minutes of operation and 1 minute stopped.

Les essais sont réalisés en alternant 2 minutes de fonctionnement et 1 minute d'arrêt.





PULMIC®
TAKE CONTROL

PULMIC INDUSTRIAL 15

CE Certification

3-year manufacturing warranty

Chemical compatibility



PULMIC®
TAKE CONTROL

PRINCIPIO ACTIVO ACTIVE PRINCIPLE Matière principale	COMPUESTO ACTIVO ACTIVE COMPOUND Matière active	INDUSTRIAL 15 INDUSTRIAL 35
ÁCIDOS ACIDS Acides	ÁCIDO ACÉTICO / ACETIC ACID / ACIDE ACÉTIQUE (MAX 20%)	×
	ÁCIDO CLORHÍDRICO / HYDROCHLORIC ACID / ACIDE CHLORHYDRIQUE (MAX 30%)	×
	ÁCIDO FLUORHÍDRICO / HYDROFLUORIC ACID / ACIDE FLUORHYDRIQUE (MAX 20%)	×
	ÁCIDO FOSFÓRICO / PHOSPHORIC ACID / ACIDE PHOSPHORIQUE	×
	ÁCIDO NÍTRICO / NITRIC ACID / ACIDE NITRIQUE (MAX 20%)	×
	ÁCIDO SULFÚRICO / SULPHURIC ACID / ACIDE SULFURIQUE (MAX 30%)	×
	BISULFITO SÓDICO / SODIUM BISULPHATE / ACIDE SODIQUE (MAX 20%)	×
	ÁCIDO OXÁLICO / OXALIC ACID / ACIDE OXALIQUE	×
ALCOHOLES ALCOHOLS Alcools	BUTANOL / BUTANOL / BUTANOL	▲
	ETANOL / ETHANOL / ÉTHANOL	▲
	METANOL / METHANOL / MÉTANOL	▲
HIDROCARBUROS ALIFÁTICOS ALIPHATIC HYDROCARBONS Hydrocarbures aliphatiques	DECANO / DECANE / DÉCANE	▲
	HEPTANO / HEPTANE / HEPTANE	▲
	HEXANO / HEXANE / HEXANE	▲
	PENTANO / PENTANE / PENTANE	▲
HIDROCARBUROS AROMÁTICOS AROMATIC HYDROCARBONS Hydrocarbures aromatiques	LIMONENO (DIPTENO) / LIMONENE (DIPTENE) / LIMONÈNE	▲
	NAFTALENO / NAPHTHALENE / NAPHTALÈNE	▲
	TOLUENO / TOLUENE / TOLUÈNE (MAX 40%)	▲
	XILENO / XYLENE / XYLÈNE	▲
ACEITES Y DERIVADOS PETRÓLEO OILS & PETROLEUM PRODUCTS Huiles et Dérivés Pétrole	ACEITE MINERAL-VEGETAL / MINERAL-VEGETAL OIL / HUILE MINÉRALE-VÉGÉTALE	✓
	GASOIL / DIESEL / GASOIL	✓
	GASOLINA / GASOLINE / ESSENCE	✓
	QUEROSENO / KEROSENE / KÉROSÈNE	✓
ALCALINOS Y CETONAS ALKALINES & KETONES Alcalins et Cétones	ACETONA / ACETONE / ACÉTONE	×
	AMONIACO / AMMONIA / AMMONIAQUE	▲
	HIDRÓXIDO DE SODIO / SODIUM HYDROXIDE / HYDROXYDE DE SODIUM	×
	HIDRÓXIDO DE POTASIO / POTASSIUM HYDROXIDE / HYDROXYDE DE POTASSIUM	×
	HIPLOCLORITO DE SODIO / SODIUM HYPOCHLORITE / HYPOCHLORITE DE SODIUM	▲



RECOMENDADO
RECOMMENDED/RECOMMANDÉ



LIMITADO
LIMITED/LIMITÉ



PROHIBIDO
FORBIDDEN/NON VALABLE



PULMIC INDUSTRIAL 15

CE Certification

3-year manufacturing warranty



Packaging and dimensions

Unit Net Weight	4,104 kg
Unit Gross Weight	4,97 kg
Packaging unit	1
Individual packaging dimensions	42 x 25,5 x 56 cm
Units per secondary carton	Not applicable
Secondary carton dimensions	Not applicable

Logistics data

Packaging units per m ³	16
Units per 20" container	480 units
Units per 40" container	960 units
Units per 40" HQ container	1120 units

Units per pallet (american)	40 units
Units per pallet (european)	24 units