

VWBG-V 1t-M14 : anneau émerillon à maillon, vis longueur standard

Artikel-Nr: 7910221




- Ball bearing for a shock-free rotating and turning with less friction.
- Lifting points pivots 360°.
- Suspension ring with enlarged pivoting area.
- Comprehensive range of threads and WLL (M8 – M30 bzw. 0,3 t – 5 t).
- Available as:
 - Standard Metric Thread (DIN EN 13)
 - Metric Fine Thread (DIN EN 13)
 - Coarse Pitch Thread UNC (ANSI B1.1)
- Clear marking of the minimum WLL for all loading directions. Higher WLL possible when location and installation is optimised(compare WLL chart / product information).
- Patented markings for easy determination for withdraw of service as well as the determination of the load angle.
- Rotatable at nominal WLL, 90° to the bolt-on direction.
- Variable bolt lengths available for tapped or through holes.
- Large distance between bolt-on surface and load to avoid damage.
- Non removable special bolt (this reduces the risk of improper standard bolts).
- Tested and certified by DGUV Testing specifications: GS-HM-36:2021-09
Certificate No.: HM 220055
- Quick and easy installation with just one bolt connection.
- Hand tightening with appropriate wrench is sufficient for a singular lift.
- Please observe torque instructions when lifting point is permanently installed resp. at constant swivelling operations and tilting/ turning actions.

Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

VWBG-V 1t-M14 : anneau émerillon à maillon, vis longueur standard

Artikel-Nr: 7910221



poids	0.67 kg	1.48 lbs
CMU	1000 kg	2200 lbs
T	114 mm	4-1/2"
A	13 mm	1/2"
B	46 mm	null
null	1-13/16"	null
C	38 mm	1-1/2"
D	48 mm	1-7/8"
E	41 mm	1-5/8"
F	21 mm	13/16"
G	56 mm	2-3/16"
M	M14 mm	M14